







BSD'의 주요 구성 요소는 다음과 같습니다.

## 4.2. BSD 프로젝트의 구조

BSD 프로젝트는 여러 하위 프로젝트로 구성되어 있으며, 각각은 BSD 라이선스를 따릅니다. 주요 프로젝트는 CVS, BSD, BSD 등이며, 이들은 모두 BSD 라이선스를 따릅니다.

BSD 프로젝트의 구조는 다음과 같습니다.

이 프로젝트는 BSD 라이선스를 따릅니다. 주요 구성 요소는 다음과 같습니다.

### 핵심 팀

BSD 프로젝트의 핵심 팀은 다음과 같습니다.

이 팀은 BSD 프로젝트의 주요 구성 요소입니다. 주요 구성 요소는 다음과 같습니다. (Principal Architect)는 프로젝트의 주요 구성 요소입니다. "Backing Out"은 BSD 프로젝트의 주요 구성 요소입니다.

### Core Team의 구성

FreeBSD와 NetBSD는 BSD 프로젝트의 주요 구성 요소입니다. 주요 구성 요소는 다음과 같습니다.

BSD 프로젝트의 주요 구성 요소는 다음과 같습니다.

1. 프로젝트의 주요 구성 요소는 다음과 같습니다. (Chief Architect)는 프로젝트의 주요 구성 요소입니다.
2. BSD 프로젝트의 주요 구성 요소는 다음과 같습니다.
3. 프로젝트의 주요 구성 요소는 다음과 같습니다. BSD 프로젝트의 주요 구성 요소는 다음과 같습니다.



BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X

- 4.4 BSD license and other licenses are used in BSD/OS and Mac OS X, and FreeBSD's BSD/OS license is also used
- BSD license and other licenses are used in Mac OS X and FreeBSD's BSD license is also used

### 4.4. BSD and GNU licenses

BSD license and GNU General Public License (GPL) are used in BSD/OS and Mac OS X. BSD license is a permissive license, while GPL is a copyleft license. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

### 4.5. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

### 4.6. BSD license and other licenses

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.
- BSD license and other licenses are used in BSD/OS and Mac OS X. BSD license is a permissive license, while other licenses like GPL are copyleft licenses. BSD license allows for the use of the code in both source and binary form, while GPL requires that the source code be made available to the user.

- 00000000000 00000000 BSD'00 0000000 000000 0000 00000000 000000 0000 00 0000 0000000000 0000000000 0000000000 00000000 00000000 BSD'0 00000000000 00000000 00000000000 0000000 0000000

## 4.7. BSD 000000000000 000000 0 0000000000000

BSDi 00000000 BSD/OS 00000000000 00000 00000 00000000 0000000000 00000 FreeBSD 000000000 00000 00000000 0000000000

00000000 FreeBSD, NetBSD 0 OpenBSD'0 00000000000 0000000000 000000 000000 00000 0000000000000 0000000000 0000000000000 00000 00000 0000000 00000